

ICHIRO SEIRYU ICR-1446

PCMO - API SQ-RC

Description

説明

Fully Synthetic high performance passenger car motor oil (PCMO) with standards of API SQ-RC that is developed to address the critical needs of newer vehicles in engine technology developments, including turbocharged gasoline direct injection (TGDI) engines.

API SQ-RC is a new category approach with a greater contribution to fuel economy and engine protection. Improved lubricant robustness assists in piston cleanliness and better fuel efficiency while maintaining sludge as well as wear control.

Benefits

特典

- △ Silk smooth operation for all high performance engines
- △ Greater fuel economy and fuel efficiency
- △ Enhanced overall engine cleanliness
- △ Protects against engine wear

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			1446
SAE Viscosity Grade	SAE J 300	-	5W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8547
Flash Point	ASTM D 92	°C	216
Pour Point	ASTM D 97	°C	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	86.68
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.29
Viscosity Index	ASTM D 2270	-	171
TBN	ASTM D 2896	mgKOH/g	7.2

Specifications & Recommendations

仕様と推奨事項

△ API SQ-RC

最後の変更: 29/10/2025
整理番号: 5157G3SQGF7REV1