

ICHIRO SEIRYU ICR-1457~1458

PCMO - FULLY SYNTHETIC ACEA A3/B4

Description

説明

Passenger car motor oil that is specially designed to deliver premium performance, robust protection and maximized longevity for your engine hardware. It is a full SAPS product that fulfills ACEA A3/B4 and API SP requirements along with a wide OEM specification coverage.

This product is specially formulated to provide outstanding anti-oxidation performance and sludge prevention as well as enhancing piston cleanliness. It delivers excellent wear protection and low speed pre-ignition (LSPI) protection for TGDI engines.

This is ideal for modern high-output, low-emission, super or turbo-charged DOHC or GDI engines that are commonly found in the latest European and Japanese models.

Benefits

特典

- △ Super fluidity over a wide range of temperatures and operating conditions
- △ Improved engine performance, yet energy conserving
- △ Reduced friction particularly during cold starts
- △ Excellent anti-oxidation property and protects against rust and corrosion

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-	
			1457	1458
SAE Viscosity Grade	SAE J 300	-	5W30	5W40
Density @ 15 °C	ASTM D 4052	kg/L	0.853	0.853
Flash Point	ASTM D 92	°C	216	220
Pour Point	ASTM D 97	°C	-39	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	68.2	88.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.9	14.7
Viscosity Index	ASTM D 2270	-	172	174
TBN	ASTM D 2896	mgKOH/g	11.6	11.6

Specifications & Recommendations**仕様と推奨事項**

△ ACEA	A3/B4
△ API	SP IN SAE 5W40
△ MERCEDES	MB 229.5
△ MERCEDES	MB 229.3
△ MERCEDES	MB 226.5
△ VW	502.00
△ VW	505.00
△ RENAULT	0700
△ RENAULT	0710

Suggested for the following uses**こんな用途におすすめ**

△ API	SP IN SAE 5W30
-------	----------------

最後の変更: 28-05-25
整理番号: 41625182G3SPA3B4REV1