

ICHIRO SEIRYU ICR-1540~1541

PCMO - API SP ACEA C3

説明 **Description**

Fully Synthetic Motor Oil utilizing the latest development in lubricating oil technology to maximize the protection of the newest gasoline engines by blend of Polyalphaolefins (PAO) synthetic base. It has the current highest performance specification, API SP and exceeds most demanding requirements of modern engine's emission control and oil consumption. In today's energy-conscious era, it also delivers fuel economic benefits by using effective friction reduction and load improvement agents.

This oil qualifies as a ACEA C3 oil. As a top-tier mid-SAPS lubricant, it is specially designed for high performance gasoline and light duty diesel engines where advanced aftertreatment systems such as Diesel Particulate Filter (DPFs) and Three Way Catalysts (TWC) are used. This oil also aligns well with many OEM performance specifications. It can be used in most advance European, American and Japanese cars models.

Benefits 特典

- Δ Formulated for stop and go driving conditions
- Δ Silk smooth operation for all high performance engines.
- Δ Exceeds latest global requirements for gasoline and LPG/CNG engines
- Δ Protects engines under severe driving conditions.

Typical Characteristics

典型的な特徴

| | | | | ICR- | |
|-----------------------------|--------------------|---------|-------|-------|--|
| Test Description | Method | Unit | 1540 | 1541 | |
| SAE Viscosity Grade | SAE J 300 | - | 5W30 | 5W40 | |
| Density @ 15 °C | ASTM D 4052 | kg/L | 0.854 | 0.855 | |
| Flash Point | ASTM D 92 | °C | 218 | 224 | |
| Pour Point | ASTM D 97 | °C | -42 | -42 | |
| Kinematic Viscosity @ 40°C | ASTM D 445 | cSt | 68.2 | 87.5 | |
| Kinematic Viscosity @ 100°C | ASTM D 445 | cSt | 11.8 | 14.4 | |
| Viscosity Index | ASTM D 2270 | - | 170 | 172 | |
| TBN | ASTM D 2896 | mgKOH/g | 9 | 9 | |
| HTHS | ASTM D 5481 | cР | ≥3.5 | ≥3.5 | |

ICHIRO CORPORATION 株式会社

www.ichiro-oil.com



Specifications & Recommendations

仕様と推奨事項

| | | 5W30 | 5W40 |
|---|---------------|---------------|---------------|
| Δ | API | SP | SP |
| Δ | ACEA | C3 | C3 |
| Δ | ILSAC | GF-6A | - |
| Δ | BMW | LL-04 | LL-04 |
| Δ | MERCEDES BENZ | 229.31 | 229.31 |
| Δ | MERCEDES BENZ | 229.51 | 229.51 |
| Δ | MERCEDES BENZ | 229.52 | 229.52 |
| Δ | OPEL | OV0401547 D30 | - |
| Δ | OPEL | OV0401547 G30 | - |
| Δ | OPEL | - | OV0401547 D40 |
| Δ | OPEL | - | OV0401547 G40 |
| Δ | RENAULT | 0700 | 0700 |
| Δ | RENAULT | 0710 | 0710 |

最後の変更: 27-08-25

整理番号: 5170G34SPC3REV1