

ICHIRO SEIRYU ICR-1225~1227 & ICR-1229

PMCO - API SL

Description

説明

Hydrotreated Passenger Car Motor Oil delivering optimum lubricating oil technology to maximize the protection of engines fuelled by gasoline, diesel, LNG and CNG operating under severe conditions. By meeting API SL, this product's performance meets engine demands in relation to engine emission control, oil consumption and volatility.

Benefits

特典

- △ Formulated for stop and go driving
- △ Silk smooth operation and high performance engines
- △ Exceeds the standards for gasoline and LNG/CNG engines
- △ Protects engines under severe driving conditions

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-			
			1225	1226	1227	1229
SAE Viscosity Grade	SAE J 300	-	10W30	10W40	15W40	20W50
Density @ 15 °C	ASTM D 4052	kg/L	0.871	0.871	0.879	0.885
Flash Point	ASTM D 92	°C	216	218	220	248
Pour Point	ASTM D 97	°C	-30	-30	-27	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	78.7	101.6	113.6	180.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.9	14.6	14.9	19.5
Viscosity Index	ASTM D 2270	-	146	149	135	123

Specifications & Recommendations

仕様と推奨事項

Δ API	SL/CF
Δ JASO	MA

最後の変更: 28-04-25
整理番号: 4121G2SLCFREV0