

ICHIRO SEIRYU 1381

PCMO - API SP ACEA A3/B4

Description

説明

Synthetic Passenger car motor oil delivering the latest development of lubricating oil technology to maximize protection for the newest gasoline fueled engines. It meets the highest performance level of API SP and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this product is also formulated to improve fuel efficiency for consumers.

Benefits

特典

- △ Silky smooth operation for all high performance engines
- △ Increases emission system durability and improves fuel efficiency
- △ Improves piston cleanliness and increases engine sludge protection
- △ Provides wear protection and extends service life

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			1381
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8692
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	98.38
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.57
Viscosity Index	ASTM D 2270	-	154
TBN	ASTM D 2896	mgKOH/g	11.6

Specifications & Recommendations

仕様と推奨事項

- △ ACEA A3/B4
- △ API SP
- △ MERCEDES BENZ MB 229.3
- △ VOLKSWAGEN 501.01/505.00

最後の変更: 22-10-24
整理番号: 5182G23SPA3B4REV0