

# ICHIRO SEIRYU ICR-2651 & 2654~2655

MCO - API SP JASO MA2

## Description

説明

**Fully Synthetic Motor Oil formulated using high quality base oils and ester in combination with a superior additive package that meets the requirement of engines that operates for a long period of time. It meets API SP and JASO MA2 performance levels and exceeds the most demanding requirements in relation to modern engine's emission control as well as oil consumption.**

Specifically developed for the stringent lubricating requirements of the ever improving sophisticated modern 4-stroke motorcycle engines, especially those used for racing. The product is designed to take into account the unique transmission requirements of the much higher engine temperatures of a modern 4T motorcycle. This makes it ideal to be used in a compacted, high speed and high temperature engine and is certain to outperform other conventional 4T oils. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

## Benefits

特典

- △ Reduces engine wear and extends engine life
- △ Retards harmful deposit formation on vital engine parts
- △ Protects against rust and corrosion
- △ Delivers friction performance required to prevent wet clutch slippage

## Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-		
			2651	2654	2655
SAE Viscosity Grade	SAE J 300	-	<b>5W40</b>	<b>10W50</b>	<b>10W60</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.861	0.855	0.869
Flash Point	ASTM D 92	°C	220	238	238
Pour Point	ASTM D 97	°C	-39	-36	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	84.8	115.1	165.2
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.5	18.1	24.4
Viscosity Index	ASTM D 2270	-	178	175	180
TBN	ASTM D 2896	mgKOH/g	6.9	6.9	6.9

**Specifications & Recommendations****仕様と推奨事項**

- |        |                  |
|--------|------------------|
| △ API  | SP IN SAE 10W40  |
| △ JASO | MA2 IN SAE 10W40 |

**Suggested for the Following Uses****以下の用途におすすめ**

- |        |                          |
|--------|--------------------------|
| △ API  | SP IN SAE 10W50 & 10W60  |
| △ JASO | MA2 IN SAE 10W50 & 10W60 |

最後の変更: 9/24/2025

整理番号: 6120G35SPMA2REV3