

ICHIRO SEIRYU ICR-1430

PCMO - API SQ

Description

説明

Fully Synthetic high performance passenger car motor oil (PCMO) specifically formulated to meet the demanding requirements of modern engine technologies. It effectively reduces engine friction, contributing to improved fuel economy, particularly during cold starts, as well as across a wide range of operating temperatures.

The low viscosity grade enhances oil flow during start-up, ensures quicker oil pressure buildup, enables faster engine response, and supports quicker attainment of optimal operating temperatures. Additionally, it helps prolong engine life by preventing the formation of harmful deposits and sludge buildup.

Benefits

特典

- △ Delivers high lubrication reliability for consistent engine performance
- △ Contributes to improved fuel economy and fuel efficiency
- △ Enhanced overall engine cleanliness for optimal operation
- △ Protects against engine wear

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			1430
SAE Viscosity Grade	SAE J 300	-	0W8
Density @ 15 °C	ASTM D 4052	kg/L	0.847
Flash Point	ASTM D 92	°C	205
Pour Point	ASTM D 97	°C	-42
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	23.8
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.0
Viscosity Index	ASTM D 2270	-	137
TBN	ASTM D 2896	mgKOH/g	8

Specifications & Recommendations

仕様と推奨事項

- △ API SQ-RC
- △ JASO GLV-1

最後の変更: 10/6/2025
整理番号: 4166G3SQGLV-1REV0