

ICHIRO SUZAKU ICR-3464

DMO - API CK-4

Description

説明

Fully Synthetic Ultra High Performance Diesel (UHPD) low ash lubricant that suggested for ACEA E6 and MB-Approval 228.51 as well as Scania Low Ash. It is blended only using high quality synthetic base fluid and advance high technology core additive package. The oil improves engine performances that are being addressed include oxidation stability, shear stability and aeration control.

The product provides high temperature protection in all grades, exceeding the tough standards against thermal breakdown. It can dramatically reduce the carbon deposit created at today's escalated operating temperature, therefore greatly reduced oil consumption so that the oil's drain interval can be extended much longer than conventional mineral based diesel engine oil.

The diesel engines oil meets Euro V and VI emission requirements that run under severe operating conditions. Suitable for use with NOx reduction systems and particulate filters as well as designed for use in combination with low sulfur diesel fuel (maximum 50 ppm).

Benefits

特典

- △ Formulated specially for use in HD Diesel engine with after treatment devices
- △ Satisfying many diesel engine OEM oil demand
- △ Provide superb performance in a very long drain interval
- △ Particular suitable for the latest diesel engine meeting EURO V and VI emission requirement.

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			3464
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.871
Flash Point	ASTM D 92	°C	228
Pour Point	ASTM D 97	°C	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	94.4
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.7
Viscosity Index	ASTM D 2270	-	162
TBN	ASTM D 2896	mgKOH/g	13.2

Specifications & Recommendations**仕様と推奨事項**

△ API	CK-4
△ ACEA	E4
△ ACEA	E6
△ ACEA	E7
△ ACEA	E9
△ CATERPILLAR	ECF-3
△ CUMMINS	CES 20081
△ CUMMINS	CES 20086
△ DETROIT DIESEL	DFS 93K222
△ DEUTZ	DQC IV-10 LA
△ JASO	DH-2
△ MACK	EOS-4.5
△ MACK	EO-O PREMIUM PLUS
△ MAN	M3477
△ MERCEDES BENZ	MB 228.31
△ MERCEDES BENZ	MB 228.51
△ MTU	CATEGORY 3.1
△ MTU	CATEGORY 2.1
△ RENAULT TRUCKS	RLD-4
△ SCANIA	LOW ASH
△ VOLVO	VDS-4.5
△ VOLVO	VDS-4

Suggested For The Following Uses**以下の用途に推奨**

△ CUMMINS	CES 20087
△ MAN	M3575
△ MAN	M3297-1

最後の変更: 1/7/2025
整理番号: 5144G3CK4E6REV0