

# ICHIRO SEIRYU 1378, 1379, 1381

PCMO - API SP ACEA A3/B4

## Description

説明

Synthetic Passenger car motor oil delivering the latest development of lubricating oil technology to maximize protection for the newest gasoline fueled engines. It meets the highest performance level of API SP and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this product is also formulated to improve fuel efficiency for consumers.

## Benefits

特典

- △ Silky smooth operation for all high performance engines
- △ Increases emission system durability and improves fuel efficiency
- △ Improves piston cleanliness and increases engine sludge protection
- △ Provides wear protection and extends service life

## Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-		
			1378	1379	1381
SAE Viscosity Grade	SAE J 300	-	<b>5W30</b>	<b>5W40</b>	<b>10W40</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.861	0.862	0.869
Flash Point	ASTM D 92	°C	214	210	218
Pour Point	ASTM D 97	°C	-36	-36	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	84.6	69.7	98.4
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.2	11.9	14.6
Viscosity Index	ASTM D 2270	-	175.0	167.0	154.0
TBN	ASTM D 2896	mgKOH/g	11.6	11.6	11.6

## Specifications & Recommendations

仕様と推奨事項

- △ ACEA A3/B4
- △ API SP
- △ MERCEDES BENZ MB 229.3 IN SAE 5W30
- △ MERCEDES BENZ MB 229.3 IN SAE 10W40
- △ VOLKSWAGEN 502.00/505.00 IN SAE 5W30
- △ VOLKSWAGEN 501.01/505.00 IN SAE 10W40

## Suggested For The Following Uses

こんな用途におすすめ

△ ACEA                    A3/B4 IN SAE 5W40  
△ API                        SP IN SAE 5W40

最後の変更: 11/9/2025  
整理番号: 5182G23SPA3B4REV1