

# ICHIRO BYAKKO ICR-5307

TRANSMISSION - ATF LT

## Description

説明

**Automatic transmission fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing for very high performance needed for the demanding requirements of passenger cars automatic gearboxes. It can be used in a broad range of automatic transmission standards and provides excellent service in a wide variety of North American, European, and Asian vehicles. It is particularly suitable for 4 and 5 speeds automatic transmissions.**

This oil is recommended for applications requiring Esso LT 71141, based on builder claims. It is suitable for use where MB 236.11 specifications are required, and for automatic transmissions specifying Volkswagen TL 52162.

## Benefits

特典

- △ Provides excellent oxidation and thermal stability for longer life
- △ Superior wear protection to protect critical transmission components
- △ Excellent viscosity stability (high VI)
- △ Much enhanced fluidity at very low temperature service

## Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			5307
Density @ 15 °C	ASTM D 4052	kg/L	0.853
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	38.1
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.2
Viscosity Index	ASTM D 2270	-	157.0

## Specifications & Recommendations

仕様と推奨事項

- △ ESSO LT 71141

最後の変更: 19/1/2024  
整理番号: 4807G23REV1