

ICHIRO BYAKKO ICR-5402

TRANSMISSION - ATF FZ

Description

説明

Automatic transmission fluid is formulated to deliver stable frictional performance, smooth gear shifting, and long-lasting protection in modern automatic transmissions. Designed with carefully selected base oils and advanced additive technology, it provides reliable performance for applications requiring a low-viscosity ATF.

The fluid offers strong resistance to oxidation and thermal degradation, helping maintain transmission cleanliness and durability even under severe operating conditions. Its stable viscosity characteristics support consistent lubrication across a wide temperature range, ensuring dependable operation during both cold starts and high-load driving.

Benefits

特典

- △ Smooth and consistent shifting
- △ Improved wear protection
- △ Excellent oxidation and thermal stability
- △ Good low-temperature fluidity

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			ICR-5402
Density @ 15 °C	ASTM D 4052	kg/L	0.850
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	27.1
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.8
Viscosity Index	ASTM D 2270	-	163.0
Appearance	Visual	-	Blue

Specifications & Recommendations

仕様と推奨事項

- △ MAZDA FZ

最後の変更: 24/12/2025
整理番号: 5392G3REV0